

# T estpassport考試指南



---

品 質 更 高 服 務 更 好

一年免費更新服務

<http://www.testpassport.net>

**Exam** : **1Z0-878**

**Title** : Oracle Solaris 10 System  
Administrator Certified  
Professional Exam, Part II

**Version** : Demo

1.DRAG DROP

Place each syslogd severity level on the correct description.

| Severity Level | Description   |
|----------------|---|
| emerg          | Other errors  |
| alert          | Panic conditions that are normally broadcast to all users         |
| err            | Conditions that are not errors but might require special handling |
| notice         | Conditions that should be corrected immediately                   |

**Answer:**

Place each syslogd severity level on the correct description.

| Severity Level | Description |
|----------------|-------------|
| emerg          | emerg       |
| alert          | err         |
| err            | alert       |
| notice         | notice      |

2.The security administrator wants to assign user bob to a netsec role so that the user can run the ifconf ig (iM) and snoop (iM) commands with a rights profile named NSM.

Which entries will be contained in the /etc/security/exec\_attr file after the required RBAC configuration has been implemented when using privileges rather than uid 0?

- A. NSM:suser:cmd:::/sbin/ifconfig:privs=sys\_net\_conf ig NSM:suser:cmd::: Aisr/sbin/snoop:privs=net\_rawaccess
- B. HSM:bob:cmd:::/sbin/ifconfig:privs=sys\_net\_config NSM:bob:cmd::: Aisr/sbin/snoop:privs=net\_rawaccess
- C. HSM:netsec:cmd:::/sbin/ifconfig:privs=sys\_net\_config NSM:netsec:cmd::: Aisr/sbin/snoop:privs=net\_rawaccess
- D. NSM:Solaris:cmd:::/sbin/ifconfig:privs=sys\_net\_config NSM:Solaris:cmd::: Aisr/sbin/snoop:privs=net\_rawaccess

**Answer: D**

3. Given the command and output:

```
# profiles -1 testrole
```

Audit Control:

```
/etc/init.d/audit uid=0, egid=3 /etc/security/bsmconv uid=0 /etc/security/bsmunconv uid=0
```

```
/usr/sbin/audit uid=0 /usr/sbin/auditconfig uid=0 /usr/sbin/auditd uid=0
```

All:

And given the fact that testrole executes commands with a profile shell, with what effective UID and real UID will the /usr/sbin/auditd program be started?

- A. effective UID 0 and real UID 0
- B. effective and real UID of testrole
- C. effective UID of testrole and real UID 0
- D. effective UID 0 and real UID of testrole

**Answer: A**

4. Given the entry from the /etc/user\_attr file:

```
User10:::profiles=User Security,Maintenance and Repair;roles=MediaAdmin;type=normal
```

Which statement is correct?

- A. The user10 account is a role account.
- B. The MediaAdmin role is defined in the /etc/security/auth\_attr file.
- C. The User Security, Maintenance and Repair profile is defined in the /etc/security/prof\_attr file.
- D. The User Security and Maintenance and Repair profiles are defined in the /etc/security/prof\_attr file.

**Answer: D**

5. On a Solaris 10 OS, you want to enable a syslog message for all incoming inetd requests.

Which command do you need to execute?

- A. inetadm - Mtcp\_trace=true
- B. inetadm - Mtcp\_wrappers=true
- C. edit /etc/inetd.conf and add a tcp wrapper to each enabled service
- D. edit /etc/init.d/inetsvc and add the -t option to the inetd invocation

**Answer: A**