TESTPASSPORT

練 習 題

質 量 更 高 | 服 務 更 好

https://www.testpassport.net

免費一年更新服務

Exam : **642-737**

Title : Implementing Advanced Cisco Unified Wireless

Version : DEMO

1.Which two considerations must a network engineer have when planning for voice over wireless roaming? (Choose two.)
A. Roaming with only 802.1x authentication requires full reauthentication.
B. Full reauthentication introduces gaps in a voice conversation.
C. Roaming occurs when e phone has seen at least four APs.
D. Roaming occurs when the phone has reached -80 dBs or below.
Answer: A,B

2.Which three of the items listed are required configuration parameters for the WLC to enable NAC out-of-band single sign-on when implementing NAC appliances? (Choose three.)
A. EAP authentication
B. web authentication
C. SNMP
D. RADIUS accounting
E. WLAN > SNMP NAC enabled
F. WLAN > RADIUS NAC enabled
Answer: C,D,E

3.An engineer is responding to a man-in-the-middle attack and needs to enable security features to prevent such attacks in the future. What security feature would prevent a manin-the-middle attack?
A. Management Frame Protection
B. ACL
C. Enable client and infrastructure MFP
D. AAA Override
Answer: C

4.Refer to the exhibit.



What is the effect of setting Client Exclusion to Enabled and set to a Timeout Value of 0 seconds in a Cisco WLC v7.0?

A. Excluded clients must be manually removed from the excluded list.
B. Client exclusion will not occur.
C. Client exclusion timeout will be determined by the IDS module.
D. Clients will only be disconnected and not excluded.
Answer: A

5.What NAC appliance component is configured to create user roles, meet remediation requirements, and handle checking for device compliance?
A. NGS
B. NAA
C. NAS
D. NAM
Answer: D