

T estpassport考試指南



品 質 更 高 服 務 更 好

一年免費更新服務

<http://www.testpassport.net>

Exam : **HP0-A17**

Title : Install, Maintain and
Upgrade Nonstop Himalaya
Hardware

Version : DEMO

1.Which tool can be used to force a reboot of a SWAN/SWAN 2 CLIP?

- A.WANDUMP
- B.WANFBT
- C.WANLNCK
- D.WANTCB

Correct:B

2.Which components can you install on the system console using the OSM Installer DVD ? (Select two.)

- A.Event Viewer
- B.Low Level Link
- C.Notification Director
- D.Service Connection

Correct:B C

3.When replacing a PMF, within how much time must the power cable be reconnected?

- A.15 seconds
- B.20 seconds
- C.25 seconds
- D.30 seconds

Correct:C

4.What is used to replace a SWAN/SWAN2 concentrator?

- A.WAN Wizard PRO
- B.Guided Procedures
- C.SCF
- D.SP Tool

Correct:C

5.The SP Tool has identified a faulty X fabric cable between enclosure 1 and enclosure 3. Which connector on the SEB in enclosure 1 is affected?

- A.1
- B.2
- C.3
- D.4

Correct:B

6.Using the HP suggested naming convention, identify the G4SA group, module, slot and port number of LIF L112E.

- A.GRP-11, MOD-2, SLOT-2, PORT-E
- B.GRP-112, MOD-2, SLOT-2, PORT-E
- C.GRP-11, MOD-2,SLOT-2, PORT-A
- D.GRP-112, MOD-2, SLOT-2, PORT-A

Correct:C

7.Which action is required before replacing an X Fabric fiber-optic cable between MSEB and Switch-to-Node ports?

- A.Verify that internal Y fabric for all other nodes are fully operational.
- B.Verify that external Y fabric for all other nodes are fully operational.
- C.Verify that both internal and external Y fabric for all other nodes are fully operational.

D. Verify that both external X and Y fabric for all other nodes are fully operational.

Correct: C

8. Which preventive maintenance tasks are performed on an S-series server? (Select two.)

- A. testing the fiber optic cables
- B. cleaning tape drives regularly
- C. running diagnostics on all devices
- D. dusting or cleaning enclosures as needed
- E. running traces on all communication lines

Correct: B D

9. To display all of the Fiber Channel Disks installed on the system along with their path states, what step(s) must be taken from the OSM Service Connection?

- A. Click the Logical Status icon, logon using the pop-up window, and then click on the FC Disk resource type.
- B. Click the Display icon and then choose the Attributes menu selection.
- C. Click the Summary icon and then choose the Connection Status menu selection.
- D. Click the Tools icon and then choose the Physical Configuration Tool menu selection.

Correct: A

10. To view the entire hardware inventory of the system, what steps must be taken?

- A. Select the system item in the hierarchical view, and then use the display Menu attributes item.
- B. Right-click on the system item in the hierarchical view, and then select the attributes sub-menu item.
- C. Double-click on the system item in the hierarchical view.
- D. Select the system item in the hierarchical view, and then change the view from physical to inventory.

Correct: D

11. Which parameters may be used to initiate a search in the TSM/OSM Event Viewer?

- A. time frame, node number, system number
- B. time frame, cluster number, SYSnn
- C. time frame, system name, timezone offset
- D. time frame, source, subsystem

Correct: D

12. Which utility displays the network route between the user's host and a remote host?

- A. PING
- B. trace
- C. tracer
- D. ptrace

Correct: C

13. What can be used to test a tape drive while troubleshooting a NonStop S-series system? (Select two.)

- A. SP Tool
- B. TFDS
- C. backup/restore
- D. tapecom
- E. OSM Service Connection

Correct: C E

14. Where can Automatic Data Collection be enabled?

- A.TACL
- B.SCF
- C.OSM Service Connection
- D.OSM Low Level Link

Correct:C

15.Which OSM file is needed for analysis of a Hardware Error Freeze (HEF) on an S-series system?

- A.ZZPSnnnn
- B.ZZAAnnnn
- C.ZZSAAnnnn
- D.CONFxyxy

Correct:A

16.Which object in OSM Service Connection displays enclosure voltages?

- A.PMF
- B.PMCU
- C.processor
- D.power supply

Correct:A

17.If you suspect a problem with a disk adapter, which subsystems in OSM Event Viewer should you select to view applicable events? (Select two.)

- A.SMD
- B.SLSA
- C.STORAGE
- D.IPC
- E.CPU

Correct:A C

18.An eight-processor system has all processors down with software halts. A tape drive is connected to the PMF 1.1.50. Which processors can be dumped to tape?

- A.Even numbered processors only.
- B.Odd numbered processors only.
- C.Processors 0 and 1 only.
- D.All eight processors in the node.

Correct:D

19.On a system where all processors are halted, which adapter locations can be specified to perform a tape dump? (Select two.)

- A.PMF 1,1,50
- B.PMF 2,1,50
- C.PMF 1,1,55
- D.PMF 11,1,50
- E.SNDA 1,1,51

Correct:A C

20.What are the three types of HotStuff messages?

- A.general, OPN, SPR recall and withdrawal
- B.general, release highlights, SPR recall and withdrawal
- C.release highlights, OPN, SPR recall and withdrawal

D.general, OPN, release highlights

Correct:A